

	A	B	C	D	E	F	G	H										
RoHS																		
1							SPECIFICATION											
2	● Voltage rating: 250V AC, DC ● Current Rating: 3.0A, AC, DC ● Withstand voltage: 1000V AC/minute ● Contact resistance: 20mΩ max ● Temperature range: -40° C ~ +105° C ● Insulation resistance: 1000MΩ min						WAFER											
3	<table border="1"> <thead> <tr> <th colspan="2">GENERAL TOLERANCE:</th> </tr> </thead> <tbody> <tr> <td>Dimensional</td> <td>±0.30</td> </tr> <tr> <td>Positioning</td> <td>±0.35</td> </tr> <tr> <td>Form</td> <td>±0.25</td> </tr> <tr> <td>Surface finish</td> <td>±0.10</td> </tr> </tbody> </table>						GENERAL TOLERANCE:		Dimensional	±0.30	Positioning	±0.35	Form	±0.25	Surface finish	±0.10	JVT2502WLP-XXSNR-S	
GENERAL TOLERANCE:																		
Dimensional	±0.30																	
Positioning	±0.35																	
Form	±0.25																	
Surface finish	±0.10																	
4							Dimensions(mm)											
Circuit		DIM.A	DIM.B	DIM.C	DIM.D													
02		2.50	7.50	10.00	8.20													
03		5.00	10.00	12.50	10.70													
04		7.50	12.50	15.00	13.20													
05		10.00	15.00	17.50	15.70													
06		12.50	17.50	20.00	18.20													
07		15.00	20.00	22.50	20.70													
08		17.50	22.50	25.00	23.20													
09		20.00	25.00	27.50	25.70													
10		22.50	27.50	30.00	28.20													
11		25.00	30.00	32.50	30.70													
12		27.50	32.50	35.00	33.20													
13		30.00	35.00	37.50	35.70													
14		32.50	37.50	40.00	38.20													
15		35.00	40.00	42.50	40.70													
16		37.50	42.50	45.00	43.20													
		JVT 乔业连接器 JVT CONNECTORS				Approved by	Check	Design										
Version		Unit mm Scale 1:1 Date 20240116				Clyde		LU										
B Adjust flatness(调整平面度) 20240116 CLYDE						P/N	JVT2502WLP-XXSNR-S											
Content of change		Date Signature					Map title	141 Version B										
A	B	C	D	E	F	G	H	I										

- Voltage rating: 250V AC, DC
- Current Rating: 3.0A, AC, DC
- Withstand voltage: 1000V AC/minute
- Contact resistance: $20\text{m}\Omega_{\text{max}}$
- Temperature range: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- Insulation resistance: $1000\text{M}\Omega_{\text{min}}$

- Material: Base: LCP UL94V-0(natural)
pin: Brass/Tin-plated
Solder: Brass/Tin-Plated

东莞市乔业电子有限公司
WWW.JYT.LTD
2024.01.16
工程发行章

Circuit	Dimensions(mm)			
	DIM. A	DIM. B	DIM. C	DIM. D
02	2.50	7.50	10.00	8.20
03	5.00	10.00	12.50	10.70
04	7.50	12.50	15.00	13.20
05	10.00	15.00	17.50	15.70
06	12.50	17.50	20.00	18.20
07	15.00	20.00	22.50	20.70
08	17.50	22.50	25.00	23.20
09	20.00	25.00	27.50	25.70
10	22.50	27.50	30.00	28.20
11	25.00	30.00	32.50	30.70
12	27.50	32.50	35.00	33.20
13	30.00	35.00	37.50	35.70
14	32.50	37.50	40.00	38.20
15	35.00	40.00	42.50	40.70
16	37.50	42.50	45.00	43.20

				GENERAL TOLERANCE		JVT 乔业连接器 JVT CONNECTORS CONNECTORS					Approved by	Check	Design	Standard	2.5mm WAFER 90°			
				0	±0.50													
				.0	±0.35													
B	Adjust flatness(调整平面度)	20240116	CLYDE	.00	±0.25													
Version	Content of change	Date	Signature		Unit	mm	Scale	1:1	Date	20240116	CLYDE	LU	P/N	JVT2502WLP-XXSNR-S				
													Map title	141	Version	B		